



www.fullstrikegroup.com

PAGE 02





www.fullstrikegroup.com





5in1-14 Product parameters

1. USB*2. High speed USB. Power supply up to 4.5W max. 2. VSB-C Female Pert1: 20/03A-Support max 87W power adapter. 3. VSB-C Female Pert2: Hight speed USB-C. Power supply up to 4.5W max. 4. USB-C Male Computable with Hundrethold 3. Make sure that the host USB-C on pour device complexes with the USB-C on pour device complexes with supply 1. Supplication

Comply with USB-C interface specification built in conversion chip. plug and play





5in1-16

Product parameters 1.05812: Hight speed USB. Priver supply up to 4.5W max. 2.056erent 10:1001000 Gigalst Elsemet 3.058-C Frenkis Piert 2.058-C Frenkis Piert 2.058-C Male: Conspatible with thurdertool 3. Male sure that the frent Sure that the frent sure that the frent Sure the frent sure that the frent sure the fre

your device complian with the USB3.0r3.1 Specification

Comply with USB-C interface specification built in conversion chip, plug and play



www.fullstrikegroup.com

5in1-13 Product parameters

1. USB*4 Hight loped USB Power supply up to 3.5W max. 2. VSB-CFreesle pert: 27/VSB-Support max EW power adapter 3. VSB-C Male: Compatible with the deviced 1. Male sum that the twel USB-C am part therito excited the USB-D (3). 1. Specification

Comply with USB-C interface specification built in conversion chip, plug and play



12 T



5in1-15

Product parameters

1. USD*4. Hight spect USD Prover supply up to 4.5W max. 2. Micro Dirg (A power adapter 3. USB-C Main: Compatibility with thunderfuel 3.Mains sum that the heat USB-C has your device compliane with the USB3.0%. Togenification.

Comply with USB-C interface specification built in conversion chip, plug and play



-

PAGE 04 HUB

6in1-6

2.US8 X.3:

1.Ethernet 10/100/1000 Gigalist Ethernet

Product parameters

www.fullstrikegroup.com





9in1-2	
Product parameters	
1.40ML 4K°24(3840°2160), Downwards, Compatible With 1060P 720P ato	Aluminum shell silm 105+44, 0+13, beam
1.05873	E and a set
Hight speed USB. Power supply spite 4.3W max.	
1.018-5 Female Pert	4
27/@IA.Support nov ETW power adapter	
4.USB+C Male	
Compatible with thumlarboil 3 Maks sure that the heat USB-C on your device complies with the USB3 X13 1 Specification	()
5.Ethernel:	
10/100/1000 Gigabit Ethernel	
a. SD/TF Card Reader:	
Support multiple types of TF and SO sants, SO cant and TF cant cannot used at the same time.	
1.0C 3.5Audie:	
3. Smith Audile Dugual	228
Comply with USB-Cinterface operification built in conversion chip, plug and play	





12in1-2 Product parameters

LHEND	
	(*2180) Description Competitive Web 1080P 725P etc.
1.018"4	
inght Asses	155 Preser suggits on to 4 Tel read
1158-674	Mala Part 1
291(2.55)	Superint Ingel RTW preser adapter
108-674	main Pert 2
Hahlese	ed USB-C Prover suppry up to 4.99 max.
4.UtB.CH	4
	with their dealbook 3. Makes pure that the heat USB Cont
prod the rise	complian with the USES I/S 1 Specification
Litternet	
101001082	Lapid Eliverse
4.50/TFE#	d Reader'
Boggert ma	Right Subsect of TP and GD samp. 300 cards and TP
part canno	used at the same time.
7 DC 1384	
3 Sten Aut	in Output
sits.	
10807-0880	No. downward compatities with 1080P. 10800.720P
	AGA support 1080P almultaneous surgus
Campigwill	1258-Convertance specification
Built in Long	ersian chip, plug and pluy



■(雪)雪(鹿)県・



10in1 Product parameters

1.4046 44/29(3640/2100),Downwards Comparitive Web 1080P 720P als: 2.45843 44: "XA(344)" (10%) Desemble Compatible With 1080P 720P and 21/04P 4
USB C Peaked USB Prevent supply cyclic LSW max. 21/04P C Peaked Prevent State Prevent State Prevent 21/04P C Peaked Prevent State Prevent State Prevent 20/04P C Peaked Prevent State Prevent State Prevent State Prevent 20/04P C Peaked Prevent State Prevent State Prevent State Prevent 21/04P C Peaked Prevent State Prevent State Prevent State Prevent 21/04P C Peaked Prevent State Prevent State Prevent State Prevent 21/04P C Peaked Prevent State Prevent State Prevent Prev 1060PgR0Hz downward comparison with 1080P tolds.120P HDFV and VGA support 1080P simultaneous subjet. Comply with USB-C interface specification built in conversion chip, plug and play





www.fullstrikegroup.com

. . .



SB-C HUR TO HDAIL+ DSB + PD	
HOMI K*2K (3840*2180), Drivemeande Compatition With 1080P 720P attp://	
uta	
nght spred USB Power tapply up in 4.3W max USB-C Famala port	
OVD38. Support max 87Wpreer adapter	
.958-C Hale. Iompetible with thurderboil 3, Make sure that the fust USB-C on	
our device complies with the USB3 0/3.1 Specification	
amply with DBB-E invertible specification	1 et
uitt in conversion chip, ping and play	200
	*
	-









& 8in1	
USB-C HUS HDMI + USS*2 + PD + SD + TF + RJ45	
LHDMI	~
4K*2K(3840*2180), Downwards Compatible With 1080# 729P etc.	Auminum shall size:
2.058*2	147+10+32.4mm
Hight speed USB Power supply up to 4.5W max.	
3.USB-CFemale Pert1	
20VB3A.Supportman#TWpower adapter	\frown
USB-C Female Part 2:	
Hight speed USB-C Power supply up to 4 5W max.	
A.USB-C.Mala:	
Compatible with thunderboil 3, Make sure that the host USB-C on	
your device complies with the USR3.0/1.1 Epecification	
5.Ethernet	test of test
A SO/TE Card Render	
8. Solver Cardinaseer. Support multiple types of TF and SD cards.SD card and TF	
page of the same types of the same type.	-
Comply with USB-C interface specification	
Buill in conversion only, plug and play	0/



USE-C HUE	
HCMH-USB13-USB C12+SD+TF+F245+VG4+OC3.3 Autile	
LHOM	
#K"24(3640*2160).Downwards Competitive Web 1080P 720P + 2.584*5	6c.
High's speed VOR Power sugging up to A 3W man.	
8. USB-E Female Port1	
2010/33, Support Han 874 power adapted	
1258-CFamale Part 2	
High speed USB-C Power supply up to 5.34 mps.	
A.USB-CMate	
Compatible with the vite Ibuil 2.3 Avia euro that the host USB-C on	
prior device compliane with the USB'S G/3.3 Equiphention	
8.8tharnat	
KO KOY TERE COMPANY TRANSPORT	
4.55/TP Card Reader	
Support routlight types of TF and SD cards SD card and TF card cannot used at the same time.	
THEA	
1080F050Hz, assessed sompletble with 1080P,1080F,720F HDTV and VGA support 1080P simultaneous output.	-
8.20 13Audie	-
3' Stree Auto Dugut	
Complywith USB-Comertace specification	
built in tunner of on this, plug and play	



* = = * A







* [문] 문 [<u>문</u>] 문] 문] 문






built in conversion chip, plug and play

I.HOM 4K*2K(3840*2160), Downwards Compatible With 1080P 720P atc. 2.058 Hight speed USB.Power supply up to 4.5W max 3.USB-C Female port. 20V@3A.Support max 87W power adapter 4. USB-C Male: Compatible with thurderboil 3. Make sure that the host USB-C on your device complex with the USB3.0/3.1 Specification Comply with USB-Cinterface specification







2.058

4in1-3 1.H0MI. 4K°2K(3840°2190),Downwards Compatible With 1080P 725P etc. Hight agent USB. Power supply up to 6.5W max 3.USB-C Female port: 20V@3A.Support max ETW power adapter 4. USB-E Male: Compatible with thursdarboil 3. Make sure that the host USB-C or your device compliance with the USB3.0/3 1 Specification 5.DC 3.SAudia 3 Seen Autic Output







Adapter 4in1-4 USB C TO PO+HOTV+USB'2

1.HOM

1 Addie 441 (2003) Add (2160), Downwards Compatible With 1980 (2720) etc. 2 USB X 2 Inight Japani USB Privar supply up in 4.20 men 2 USB - Changes part. 2 USB - Changes part. 2 USB - Changes part.

4. USB-C Male: Compatible with thursderbol 3,Males sure that the heat USB-C er-your device complete with the USB3 60.1 Specification

Comply with USB-Contentace operation built in conversion chip, plug and play





LHDM

LHDM: 4K*2K(3840*2180), Downwards Compatible With 1580P 725P etc. 2. USB Hight speed USB Pawer supply up to 4.5W max 3. USB-C Female port: 30V(81A Support max 87W power adapter 4.USB-CHale: Compatible with thurderboil 3 Make sure that the host USE-C us your device comprises with the USE3. D/3 1 Specification SD/TF Card Reader: Buggert multiple types of TF and SD cards.SD card and TF card carnot used at the same time.

Comply with USB-Clinterface specification built in conversion chip, plug and play



. . .





• -

HUB

www.fullstrikegroup.com





1.4040 46128(384812188), Downwards Compatible With 1880P 720P etc. 2.058 2, USB Might Speed (UB) Proved supprivate 5, SB mae 1, USB-C Famale parts 2019 15-5, Support mail: RM proved adapter 4, USB-CMate Compatible with thrundarbod 3, Make sure that the host USB-C on providevice complex with the USB3, 0/3, 5 Specification

Comply with USB-C interface specification built in conversion thip plug and play







1.HOM 4K*2K(3840*2160)30Hz and 4K*2K(3840*2160)60Hz are svallable. 2.058

Hight spent USB. Power supply up to 4.5W max. 3.USB-C Female Port

20V@3A Support max 87W power adapter.

4,USB-C Male:

copatible with thunderbuil 3 Make sure that the host USB-C port on your device complies with the USB3.0/2.15pecification

Comply with USB-C interface specification built in conversion chip plug and play



.







.



C P10-1

6.00 3.5Audie: 3.5mm Aatop Autio Dutpuk

Comply with QSB-Clinitertane specification suiti in conversion city, plug and glay

1. MERCENT

USB-C HUB TO HOM + VGA + USB + PD + 5.5Audio

4K*2K(3840*2160).Downwarts Compatitive With 1080P 720P etc. 2 USB

USB: USB: USB: USB: USB-CRewate supply up to 4.3W mus USB-CRewate parts USB-CRewate parts USB-CRewate USB-CRE

1000P@00Hz.downward.compatible.with.1080P.3080I.720P HDTV and VGA support 1080P simultaneous indput.









1.VGA 1080P@60Hz.downward.compatible.with 1080P.1080I.720P

2.USB-CMale:

Compatible with thunderboil 3, Make sure that the host USB-C on your device complies with the USB3.0/3.1 Specification





www.fullstrikegroup.com

.

HUB





4K*2K(3840*2160),Downwards Compatible With 1080P 720P etc.

2.USB-C Male: Compatible with thunderboil 3, Make sure that the host USB-C on your device complies with the US83.0/3.1 Specification

Comply with USB-C interface specification built in conversion chip, plug and play

Th13











1.058*2

5in1-17 USB C TO PO + HOMI + USB X 3

Hight speed USB Power supply up to 4.5W max 2,HDMI

4K*2K/3840*21801 Downwards Compalible With 1080P 720P etc. 3.USB-C Female port ar adapte

20V@IA Support mias 87Wp

4.USB-CMale: Con this with t bol 3. Make oure that the foot USB-C on your device complies with the USB3.0/3.1 Specification

Comply with USB-C interface specification built in conversion chip. plug and play





9 9 9 9 9





1.US8*1: Hight speed USB. Power supply up to 4.5W max. 2. US8-C Female Port1: 20V@3A.Support max 87W power adapter,

3. USB-C Female Port 2: Hight speed USB-C. Power supply up to 4.5W max. 4.USB-C Male:

Compatible with thunderboil 3. Make sure that the host USB-C on your device complies with the USB3.0/3.1 Specification

Comply with USB-C interface specification built in conversion chip, plug and play





HUB







I.HDME	1
4K*2K(3840*2160).Downwards Compatible With 1080P 720P etc.	
2.USB X 3:	
Hight speed USB. Power supply up to 4.5W max	Alternation shall size
3. USB-C.Female port:	101.35-43.20-15.604
20V@3A.Support max 87W power adapter	
4. USB-C Male:	
Compatible with thunderboil 3. Make sure that the host USB-C on	
your device complies with the USB3.0/3.1 Specification	
5.50/TF Card Reader:	0
Support multiple types of TF and SD cards.SD card and TF	
card cannol used at the same time.	
Comply with USB-C interface specification	
built in conversion chip, plug and play	
	-
	12

7in1-6

USB C TO PD+HDMI+SD+TF+USB X 3



HUB



www.fullstrikegroup.com





5in1-22 TYPE C TO TYPE C+US8+HOTV X2+VGA

1.HDM

4K12K(384012160),Downwards Competitive With 1086P 720P etc. 2. DP 4K*2K(3840*2160).Downwards Compatible With 1080P 720P etc.

MST 4in1-11 TYPE C TO HDTV+DP+MINI DP+VGA

3. MINI OP 4K*2K(3840*2160), Downwards Compatible With 1080P 720P etc.

AVGA 1040P/B60Hz downward compatible with 1040P 1080I 720P

HDTV and VGA support 1580P simultaneous subput.

5.058-C Male

Compatible with thunderboil 3.Make sure that the host USB-C o your device complies with the USB3.0/3.1 Specification

Comply with USB-C interface specification

built in conversion chip, plug and play





LHDMIX2:

4K*2X(3640*2180) Downwards Compatible With 1080P 720P etc. 2.USB: Hight speed USB.Power supply up to 4.5W max Dia c + koty 3. USB-C Female Port 20VB3A Support max 87W power adapter 4.USB-C Male Compatible with thunderboil 3. Make sure that the host USB-C on your device complies with the USB3.0/3.1 Specification 6.VGA 1080P@80Hz.downward.compatible.with 1080P,1080X.720P HOTV and VGA support 1980P simultaneous output. Comply with USB-C interface specification built in conversion chip. plug and play 00000 -----÷





HUB

MST Sin1-7 TYPE C TO TYPE C+US8X3+HOTV X2+SD+TF



www.fullstrikegroup.com

MST 9in1-4 TYPE C TO TYPE C+US8X2+HDTV X2+SD+TF+R345+VGA

L HDMS X 2 4K*2X(3845*2160).Downwards Compatible With 1085P 720P etc.	
2 US8*2:	An una c a roty
Hight speed USB Power supply up to 4.5W max, 3. USB-C Femala Port:	P
20V@3A Support max ETWpower adapter.	100
A.USB-C.Male:	
Compatible with thunderboil 3. Make sure that the host USB-C on your device complies with the USB3.0/3.1 Specification	
\$.Ethernet	
10/105/1000 Gigabit Ethionist	
& SD/TF Card Reader:	
Support multiple types of TF and SD cards SD card and TF	
card cannot used at the same time.	
7yEA 1080P (HEHz, Sownward compatible with 1080P 10801 720P	1 Departure 1
HDTV and VGA support 1080P simultaneous output.	1000000
Comply with USB-C interface specification	Million and a second second
built in conversion chip, plug and play	· · · · · · · · · · · · · · · · · · ·
	CHICKS ASSOCIATE ALTERNATION



12in 1-3 TYPE C TO TYPE CX2+USBX3+HDTV X2+SD+TF+RJ45+VGA+3.5mm Audo



MST

12in1-4 TYPE C TO TYPE CX2+USBX3+HDTV.X2+SD+TF+RU45+VGA+3.5mm Audio

1.HDMiX2:

4K*2K(3840*2160),Downwards Compatible With 108DP 720P etc. 2.058*3 ht speed USB. Power supply up to 4.5W max. USB-C Female Port1 : Compatible with thunderboil 3, Make sure that the host USB-C on your device complies with the USB3.0/3 1 Specification USB-C Female Port2: 20VIB3A Support max 87W prever adapter USB-CFemale Port 1: Hight speed USB-C Power supply up to A SW max 4.Ethernet 10/100/1006 Gigate Ethernet 5. SO/TF Card Reader: Support multiple types of TF and SD cards, SD card and TF card cannot used at the same time. A.VUA 1080Pdb60Hz.downward.compatible.with 1080P.10801.720P HDTV and VGA support 1080P simultaneous output 7.DC 1.5Audie 3. fmm Audio Output



HUB

www.fullstrikegroup.com







1.HDTV:

2.USB*3:

8in1-9

4K12K(384012160) Downwards Compatible With 1080P 720P etc. Highi speed USB.Power supply up to 4.5W max.

108 x 3+8,45+50

3.US8-C Female Port: 20V@3A.Support max #1W power adapter 4.USB-C Male: Competible with thunderboil 2 Make sure that the host USB-C on your device complies with the USB3 0/3.1 Specification 5.Ethernet: 10/100/1000 Gigabit Ethernet 6. SD/TFCard Reader: Support multiple types of TF and SO cards.SO card and TF

card cannot used at the same time

Comply with USB-C interface specification built in conversion chip. plug and play







4.USB-CHale

Compatible with thurdenbolt 3. Mate sure that the boat USB-C an your device complians with the USB3.0(3.1 Specification

5.Ethernet: 10/100/1000 Gigebit Ethernet

4.5D/TF Card Reader:

Support multiple types of TP and SD cards, SD card and TP card cannot used at the same time.

7.0C 1.5Audie : 3 Bmm Audio Output

EVGA: 1080P@80Hz.downward compatible with 1080P.10856.720F HDTV and VGA support 1080P situateneous output.

Comply with USB-C interface specification built in conversion chip. plug and play



A .

www.fullstrikegroup.com

1 HOTV:

Adapter



9in1-4

SB X 2+RJ45+SC+TF+VGA+Audia

7in1-6

ght speed US8. Power supply up to 4. IW max

20V@3A.Support max 87W power adapter

Comply with USB-C interface specification

built in conversion chip. plug and play

4K*2K(3840*2180), Downwards Competible With 1080P 720P etc

Competible with thunderboil 3. Make sure that the host USB-C on your device complies with the USB3.0-3.1 Specification

Support multiple types of TF and SD cards.SD card and TF card cannot used at the same time.

1.HOTV

2.USB*2:

2. USB-C Female Port:

5 Ethernet : 10/100/1000 Gigabit Ethernet

4. SD/TF Card Reader:

4.USB-CMale:

UND X 1-10-45-50-11

4.USB-CMate: Compatible with thunderboil 3. Make sure that the host USB-C on your device compiles with the USB3 0/3.1 Specification

5.Ethernel : 10/100/1000 Gigabit Ethernel

& 50/TF Card Reader

Support multiple types of TF and SD cards, SD card and TF card cannot used at the same time.

7.VGA: 1080P@60Hz.doemward.compatible with 1080P.10800.720P HDTV and VGA support 1080P simultaneous output

8.DC 3.5mm Audio: 3 tem Audo Oxfed



Comply with USB-C interface specification

built in conversion thip, plug and play



13



4-IN 1 USB C HUB



USB C To HDMI=USB3.0=PD+RJ45-Adapter



8-IN 1 USB C HUB



8-IN 1 USB C HUB



sales@fullstrikegroup.com www.fullstrikegroup.com



Office: Room 302, T3, Taiziwan Commercial Building, Cruise Avenue, Nanshan District, Shenzhen, China 518067.

Factory: NO.123, Jinghui west Rd, Investment entrepreneurship center, Xaying, Ynzhou, Ningbo, China.

Germany Office: Robinson Road 7, App. 10, 55768 Hoppstädten-Weiersbach Deutschland

FSL is standing in the market with "3 Best Policy" since the very first day of servicing customers:

Best Service、

Best Quality、

Best Price.

We 100% fully trust that you must enjoy doing business with us!